

## Specifications

Basic Functions	Range	Test Frequency	Best Accuracy
Resistance	10mΩ to 1Ω	100Hz	± 2% ± 3
	1Ω to 1KΩ	100Hz	± 1% ± 3
	1KΩ to 1MΩ	100Hz	± 1% ± 3
	1MΩ to 10MΩ	100Hz	± 5% ± 3
	10mΩ to 1Ω	1KHz	± 2% ± 3
	1Ω to 1KΩ	1KHz	± 0.5% ± 3
	1KΩ to 1MΩ	1KHz	± 0.5% ± 3
	1MΩ to 10MΩ	1KHz	± 5% ± 3
	10mΩ to 1Ω	10KHz	± 2% ± 3
	1Ω to 1KΩ	10KHz	± 0.5% ± 3
	1KΩ to 1MΩ	10KHz	± 1% ± 3
	1MΩ to 10MΩ	10KHz	-----
Capacitance	1pF to 1nF	100Hz	-----
	1nF to 1μF	100Hz	± 2% ± 3
	1μF to 1mF	100Hz	± 2% ± 3
	1mF to 22mF	100Hz	± 5% ± 3
	1pF to 1nF	1KHz	± 2% ± 3
	1nF to 1μF	1KHz	± 0.5% ± 3
	1μF to 1mF	1KHz	± 2% ± 3
	1mF to 22mF	1KHz	± 5% ± 3
	1pF to 1nF	10KHz	± 2% ± 3
	1nF to 1μF	10KHz	± 0.5% ± 3
	1μF to 1mF	10KHz	± 2% ± 3
	1mF to 22mF	10KHz	-----
Inductance	1uH to 10uH	100Hz	-----
	10uH to 1mH	100Hz	± 2% ± 3
	1mH to 1H	100Hz	± 2% ± 3
	1H to 10H	100Hz	± 5% ± 3
	1uH to 10uH	1KHz	-----
	10uH to 1mH	1KHz	± 0.5% ± 3
	1mH to 1H	1KHz	± 2% ± 3
	1H to 10H	1KHz	± 5% ± 3
	1uH to 10uH	10KHz	± 2% ± 3
	10uH to 1mH	10KHz	± 0.5% ± 3
	1mH to 1H	10KHz	± 2% ± 3
	1H to 10H	10KHz	-----

**Special Functions**

Diode Test	Yes
Data Hold	Yes
Auto power OFF	Yes
Low Battery Display	Yes
Max. Display	1999

**General Characteristics**

Battery	Lithium Ion	250mAH	Rechargeable
LCD Size	25 x 15	mm	
Product Net Weight	41	grams	
Product Size	150 x 28 x 15	mm	