



Drawings not to scale
All dimensions in mm (inches) nominal

UL approved

SPECIFICATION

CONTACT FORM		Installation Dependant
SWITCHING VOLTAGE	Max. V	240 Vac/200 Vdc
SWITCHING CURRENT	Max. A	0.5
CARRY CURRENT	Max. A	1.0
SWITCHING CAPACITY	Max. VA	50W
CONTACT RESISTANCE	Max. mΩ	200
LEAD WIRE		XLPE AWG22
REVERSIBLE SWITCH ACTION		YES
OPERATING PRESSURE	Max. Kg/cm ²	4.0
OPERATING TEMPERATURE	Deg. °C	-20° +80°
MATERIAL		Polypropylene
SUITABLE SPECIFIC GRAVITY		0.75
WEIGHT	gm.	22
MOUNTING HOLE DIA.	mm.	16.0

FLOAT - Reed Switch - Plastic

PART NUMBER
HFP21

Rev. No.	Revision Note	Date	Signature
A	Web Site 2003	1-7-03	RG

The Comus Group of Companies consist of:
Assemtch Europe Limited
E. Bachem GmbH
Comus International
W. Gunther GmbH
Gunther Belgium
Gunther France
S.T.G.

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.