

isc Silicon NPN Power Transistor

2SD226

DESCRIPTION


- Excellent Safe Operating Area
- Low Collector-Emitter Saturation Voltage
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation.

APPLICATIONS


- Designed for general-purpose power amplifier and switching applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	50	V
V_{CEO}	Collector-Emitter Voltage	40	V
V_{EBO}	Emitter-Base Voltage	8	V
I_C	Collector Current-Continuous	3	A
I_{CM}	Collector Current-Peak	5	A
P_C	Collector Power Dissipation@ $T_C=25^{\circ}\text{C}$	25	W
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-65~150	$^{\circ}\text{C}$



PIN 1. BASE
2. EMITTER
3. COLLECTOR (CASE)
TO-66 package



DIM	mm	
	MIN	MAX
A	31.40	31.80
B	17.30	17.90
C	6.70	7.10
D	0.70	0.90
E	1.40	1.80
G	5.08	
H	2.54	
K	9.80	10.50
L	14.70	14.90
N	12.40	12.70
Q	3.60	3.80
U	24.30	24.50
V	3.50	3.70

isc Silicon NPN Power Transistor**2SD226****ELECTRICAL CHARACTERISTICS** $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CEO(SUS)}^*$	Collector-Emitter Sustaining Voltage	$I_C=30\text{mA}; I_B=0$	40		V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E=1\text{mA}; I_C=0$	8		V
I_{EBO}	Emitter Cutoff Current	$V_{EB}=7\text{V}; I_C=0$		0.1	mA
I_{CBO}	Collector Base Cutoff Current	$V_{CB}=50\text{V}; I_E=0$		0.1	mA
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=1.5\text{A}; I_B=0.15\text{A}$		0.7	V
$V_{BE(ON)}$	Base-Emitter On Voltage	$I_C=1.5\text{A}; V_{CE}=3\text{V}$		1.4	V
h_{FE-1}^*	DC Current Gain	$I_C=1\text{A}; V_{CE}=3\text{V}$	50	200	
h_{FE-2}^*	DC Current Gain	$I_C=3\text{A}; V_{CE}=3\text{V}$	20		

*:Pulse test:Pulse width=300us,duty cycle≤2%

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.