

isc Silicon PNP Power Transistor

BD250/A/B/C

DESCRIPTION

- Collector Current $-I_C = -25A$
- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = -45V(\text{Min})$ - BD250; $-60V(\text{Min})$ - BD250A
 $-80V(\text{Min})$ - BD250B; $-100V(\text{Min})$ - BD250C
- Complement to Type BD249/A/B/C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for use in general purpose power amplifier and switching applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CE}	Collector-Emitter Voltage ($R_{BE} = 100\Omega$)	BD250	-55
		BD250A	-70
		BD250B	-90
		BD250C	-115
V_{CEO}	Collector-Emitter Voltage	BD250	-45
		BD250A	-60
		BD250B	-80
		BD250C	-100
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current-Continuous	-25	A
I_{CM}	Collector Current-Peak	-40	A
I_B	Base Current	-5	A
P_C	Collector Power Dissipation @ $T_a=25^\circ\text{C}$	3	W
	Collector Power Dissipation @ $T_c=25^\circ\text{C}$	125	
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.0	$^\circ\text{C/W}$



DIM	mm	
	MIN	MAX
A	19.60	20.30
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.20
H	3.20	3.40
J	0.595	0.605
K	19.80	20.70
L	1.90	2.20
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.100
U	5.90	6.20
Y	9.90	10.10

isc Silicon PNP Power Transistor

BD250/A/B/C

ELECTRICAL CHARACTERISTICS

T_C=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	BD250	$I_C = -30mA; I_B = 0$	-45			V
		BD250A		-60			
		BD250B		-80			
		BD250C		-100			
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage		$I_C = -15A; I_B = -1.5A$			-1.8	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage		$I_C = -25A; I_B = -5A$			-4.0	V
$V_{BE(on)-1}$	Base-Emitter On Voltage		$I_C = -15A; V_{CE} = -4V$			-2.0	V
$V_{BE(on)-2}$	Base-Emitter On Voltage		$I_C = -25A; V_{CE} = -4V$			-4.0	V
I_{CES}	Collector Cutoff Current	BD250	$V_{CE} = -55V; V_{BE} = 0$			-0.7	mA
		BD250A	$V_{CE} = -70V; V_{BE} = 0$				
		BD250B	$V_{CE} = -90V; V_{BE} = 0$				
		BD250C	$V_{CE} = -115V; V_{BE} = 0$				
I_{CEO}	Collector Cutoff Current	BD250/A	$V_{CE} = -30V; I_B = 0$			-1.0	mA
		BD250B/C	$V_{CE} = -60V; I_B = 0$				
I_{EBO}	Emitter Cutoff Current		$V_{EB} = -5V; I_C = 0$			-1.0	mA
h_{FE-1}	DC Current Gain		$I_C = -1.5A; V_{CE} = -4V$	25			
h_{FE-2}	DC Current Gain		$I_C = -15A; V_{CE} = -4V$	10			
h_{FE-3}	DC Current Gain		$I_C = -25A; V_{CE} = -4V$	5			
Switching times							
t_{on}	Turn-on Time		$I_C = -5A; I_{B1} = -I_{B2} = -0.5A; R_L = 5\Omega; V_{BE(off)} = -5V$		0.2		μs
t_{off}	Turn-off Time				0.4		μs

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.