

6

5


4

3


2

1


L±3%



Connecting



P1	568B COLOR	P2
1	WH/ORG	1
2	ORG	2
3	WH/GRN	3
4	BLU	4
5	WH/BLU	5
6	GRN	6
7	WH/BWN	7
8	BWN	8



SPECIFICATIONS:

- 1. CONDUCTOR:
 - 1.1 CONDUCTORS: 24AWG CCA 7*0.20±0.015mm
 - 1.2 CONDUCTOR INSULATION COLOR CODING: ONE WHITE/ORANGE, ONE ORANGE, ONE WHITE/GREEN, ONE GREEN, ONE BLUE, ONE WHITE/BLUE, ONE WHITE/BROWN, ONE BROWN.
- 2. CABLE JACKET
 - 2.1 PRINTING ON THE JACKET: ACCORDING TO CUSTOMER'S REQUEST
 - 2.2 JACKET COLOR: ACCORDING TO CUSTOMER'S REQUEST
- 3. CABLE ASSEMBLY
 - 3.1 SEE SECTION A-A FOR DIMENSIONS
 - 3.2 CABLE TIE: WHITE
 - 3.3 WIRING T568B PINOUT
 - 3.4 CONTACT PLUG: RJ45 8P8C UTP
- 4. CABLE JACKET COLOR: ACCORDING TO CUSTOMER'S REQUEST
- 5. LENGTH: L±3%mm
- 6. Temperature range : -20~60°

REMARK NO	CHA. NO	SIGNATURE	DATE				UTP CAT6 CABLE 24AWG
DRAWN BY				SIGN	W.T	SCALE	
CHECKED BY							CCA
AUDITED BY		APPROVED BY					
CRAFT		DATE			PAGE	OF	

6

5

4

3

2

1